



# **9600 Series IP Deskphones Overview and Specifications**

Release 7.1.5  
Issue 1  
April 2019

© 2014-2019, Avaya Inc.  
All Rights Reserved.

#### Note

Using a cell, mobile, or GSM phone, or a two-way radio in close proximity to an Avaya IP telephone might cause interference.

#### Documentation disclaimer

"Documentation" means information published in varying mediums which may include product information, operating instructions and performance specifications that are generally made available to users of products. Documentation does not include marketing materials. Avaya shall not be responsible for any modifications, additions, or deletions to the original published version of Documentation unless such modifications, additions, or deletions were performed by or on the express behalf of Avaya. End User agrees to indemnify and hold harmless Avaya, Avaya's agents, servants and employees against all claims, lawsuits, demands and judgments arising out of, or in connection with, subsequent modifications, additions or deletions to this documentation, to the extent made by End User.

#### Link disclaimer

Avaya is not responsible for the contents or reliability of any linked websites referenced within this site or Documentation provided by Avaya. Avaya is not responsible for the accuracy of any information, statement or content provided on these sites and does not necessarily endorse the products, services, or information described or offered within them. Avaya does not guarantee that these links will work all the time and has no control over the availability of the linked pages.

#### Warranty

Avaya provides a limited warranty on Avaya hardware and software. Refer to your sales agreement to establish the terms of the limited warranty. In addition, Avaya's standard warranty language, as well as information regarding support for this product while under warranty is available to Avaya customers and other parties through the Avaya Support website: <https://support.avaya.com/helpcenter/getGenericDetails?detailId=C20091120112456651010> under the link "Warranty & Product Lifecycle" or such successor site as designated by Avaya. Please note that if You acquired the product(s) from an authorized Avaya Channel Partner outside of the United States and Canada, the warranty is provided to You by said Avaya Channel Partner and not by Avaya.

"Hosted Service" means an Avaya hosted service subscription that You acquire from either Avaya or an authorized Avaya Channel Partner (as applicable) and which is described further in Hosted SAS or other service description documentation regarding the applicable hosted service. If You purchase a Hosted Service subscription, the foregoing limited warranty may not apply but You may be entitled to support services in connection with the Hosted Service as described further in your service description documents for the applicable Hosted Service. Contact Avaya or Avaya Channel Partner (as applicable) for more information.

#### Hosted Service

THE FOLLOWING APPLIES ONLY IF YOU PURCHASE AN AVAYA HOSTED SERVICE SUBSCRIPTION FROM AVAYA OR AN AVAYA CHANNEL PARTNER (AS APPLICABLE), THE TERMS OF USE FOR HOSTED SERVICES ARE AVAILABLE ON THE AVAYA WEBSITE, [HTTPS://SUPPORT.AVAYA.COM/LICENSEINFO](https://support.avaya.com/LICENSEINFO) UNDER THE LINK "Avaya Terms of Use for Hosted Services" OR SUCH SUCCESSOR SITE AS DESIGNATED BY AVAYA, AND ARE APPLICABLE TO ANYONE WHO ACCESSES OR USES THE HOSTED SERVICE. BY ACCESSING OR USING THE HOSTED SERVICE, OR AUTHORIZING OTHERS TO DO SO, YOU, ON BEHALF OF YOURSELF AND THE ENTITY FOR WHOM YOU ARE DOING SO (HEREINAFTER REFERRED TO INTERCHANGEABLY AS "YOU" AND "END USER"), AGREE TO THE TERMS OF USE. IF YOU ARE ACCEPTING THE TERMS OF USE ON BEHALF A COMPANY OR OTHER LEGAL ENTITY, YOU REPRESENT THAT YOU HAVE THE AUTHORITY TO BIND SUCH ENTITY TO THESE TERMS OF USE. IF YOU DO NOT HAVE SUCH AUTHORITY, OR IF YOU DO NOT WISH TO ACCEPT THESE TERMS OF USE, YOU MUST NOT ACCESS OR USE THE HOSTED SERVICE OR AUTHORIZE ANYONE TO ACCESS OR USE THE HOSTED SERVICE.

#### Licenses

THE SOFTWARE LICENSE TERMS AVAILABLE ON THE AVAYA WEBSITE, [HTTPS://SUPPORT.AVAYA.COM/LICENSEINFO](https://support.avaya.com/LICENSEINFO), UNDER THE LINK "AVAYA SOFTWARE LICENSE TERMS (Avaya Products)" OR SUCH SUCCESSOR SITE AS DESIGNATED BY AVAYA, ARE APPLICABLE TO ANYONE WHO DOWNLOADS, USES AND/OR INSTALLS AVAYA SOFTWARE, PURCHASED FROM AVAYA INC., ANY AVAYA AFFILIATE, OR AN AVAYA CHANNEL PARTNER (AS APPLICABLE) UNDER A COMMERCIAL AGREEMENT WITH AVAYA OR AN AVAYA CHANNEL PARTNER. UNLESS OTHERWISE AGREED TO BY AVAYA IN WRITING, AVAYA DOES NOT EXTEND THIS LICENSE IF THE SOFTWARE WAS OBTAINED FROM ANYONE OTHER THAN AVAYA, AN AVAYA AFFILIATE OR AN AVAYA CHANNEL PARTNER; AVAYA RESERVES THE RIGHT TO TAKE LEGAL ACTION AGAINST YOU AND ANYONE ELSE USING OR SELLING THE SOFTWARE WITHOUT A LICENSE. BY INSTALLING, DOWNLOADING OR USING THE SOFTWARE, OR AUTHORIZING OTHERS TO DO SO, YOU, ON BEHALF OF YOURSELF AND THE ENTITY FOR WHOM YOU ARE INSTALLING, DOWNLOADING OR USING THE SOFTWARE (HEREINAFTER REFERRED TO INTERCHANGEABLY AS "YOU" AND "END USER"), AGREE TO THESE TERMS AND CONDITIONS AND CREATE A BINDING CONTRACT BETWEEN YOU AND AVAYA INC. OR THE APPLICABLE AVAYA AFFILIATE ("AVAYA").

Avaya grants You a license within the scope of the license types described below, with the exception of Heritage Nortel Software, for which the scope of the license is detailed below. Where the order documentation does not expressly identify a license type, the applicable license will be a Designated System License. The applicable number of licenses and units of capacity for which the license is granted will be one (1), unless a different number of licenses or units of capacity is specified in the documentation or other materials available to You. "Software" means computer programs in object code, provided by Avaya or an Avaya Channel Partner, whether as stand-alone products, pre-installed on hardware products, and any upgrades, updates, patches, bug fixes, or modified versions thereto. "Designated Processor" means a single stand-alone computing device. "Server" means a Designated Processor that hosts a software application to be accessed by multiple users. "Instance" means a single copy of the Software executing at a particular time: (i) on one physical machine; or (ii) on one deployed software virtual machine ("VM") or similar deployment.

#### License types

Designated System(s) License (DS). End User may install and use each copy or an Instance of the Software only on a number of Designated Processors up to the number indicated in the order. Avaya may require the Designated Processor(s) to be identified in the order by type, serial number, feature key, Instance, location or other specific designation, or to be provided by End User to Avaya through electronic means established by Avaya specifically for this purpose.

Shrinkwrap License (SR). You may install and use the Software in accordance with the terms and conditions of the applicable license agreements, such as "shrinkwrap" or "clickthrough" license accompanying or applicable to the Software ("Shrinkwrap License").

#### Heritage Nortel Software

"Heritage Nortel Software" means the software that was acquired by Avaya as part of its purchase of the Nortel Enterprise Solutions Business in December 2009. The Heritage Nortel Software is the software contained within the list of Heritage Nortel Products located at <https://support.avaya.com/LicenseInfo> under the link "Heritage Nortel Products" or such successor site as designated by Avaya. For Heritage Nortel Software, Avaya grants Customer a license to use Heritage Nortel Software provided hereunder solely to the extent of the authorized activation or authorized usage level, solely for the purpose specified in the Documentation, and solely as embedded in, for execution on, or for communication with Avaya equipment. Charges for Heritage Nortel Software may be based on extent of activation or use authorized as specified in an order or invoice.

#### Copyright

Except where expressly stated otherwise, no use should be made of materials on this site, the Documentation, Software, Hosted Service, or hardware provided by Avaya. All content on this site, the

documentation, Hosted Service, and the product provided by Avaya including the selection, arrangement and design of the content is owned either by Avaya or its licensors and is protected by copyright and other intellectual property laws including the sui generis rights relating to the protection of databases. You may not modify, copy, reproduce, republish, upload, post, transmit or distribute in any way any content, in whole or in part, including any code and software unless expressly authorized by Avaya. Unauthorized reproduction, transmission, dissemination, storage, and or use without the express written consent of Avaya can be a criminal, as well as a civil offense under the applicable law.

### Virtualization

The following applies if the product is deployed on a virtual machine. Each product has its own ordering code and license types. Note that each Instance of a product must be separately licensed and ordered. For example, if the end user customer or Avaya Channel Partner would like to install two Instances of the same type of products, then two products of that type must be ordered.

### Third Party Components

"Third Party Components" mean certain software programs or portions thereof included in the Software or Hosted Service may contain software (including open source software) distributed under third party agreements ("Third Party Components"), which contain terms regarding the rights to use certain portions of the Software ("Third Party Terms"). As required, information regarding distributed Linux OS source code (for those products that have distributed Linux OS source code) and identifying the copyright holders of the Third Party Components and the Third Party Terms that apply is available in the products, Documentation or on Avaya's website at: <https://support.avaya.com/Copyright> or such successor site as designated by Avaya. The open source software license terms provided as Third Party Terms are consistent with the license rights granted in these Software License Terms, and may contain additional rights benefiting You, such as modification and distribution of the open source software. The Third Party Terms shall take precedence over these Software License Terms, solely with respect to the applicable Third Party Components to the extent that these Software License Terms impose greater restrictions on You than the applicable Third Party Terms.

The following applies only if the H.264 (AVC) codec is distributed with the product. THIS PRODUCT IS LICENSED UNDER THE AVC PATENT PORTFOLIO LICENSE FOR THE PERSONAL USE OF A CONSUMER OR OTHER USES IN WHICH IT DOES NOT RECEIVE REMUNERATION TO (i) ENCODE VIDEO IN COMPLIANCE WITH THE AVC STANDARD ("AVC VIDEO") AND/OR (ii) DECODE AVC VIDEO THAT WAS ENCODED BY A CONSUMER ENGAGED IN A PERSONAL ACTIVITY AND/OR WAS OBTAINED FROM A VIDEO PROVIDER LICENSED TO PROVIDE AVC VIDEO. NO LICENSE IS GRANTED OR SHALL BE IMPLIED FOR ANY OTHER USE. ADDITIONAL INFORMATION MAY BE OBTAINED FROM MPEG LA, L.L.C. SEE [HTTP://WWW.MPEGLA.COM](http://www.mpegla.com).

### Service Provider

THE FOLLOWING APPLIES TO AVAYA CHANNEL PARTNER'S HOSTING OF AVAYA PRODUCTS OR SERVICES. THE PRODUCT OR HOSTED SERVICE MAY USE THIRD PARTY COMPONENTS SUBJECT TO THIRD PARTY TERMS AND REQUIRE A SERVICE PROVIDER TO BE INDEPENDENTLY LICENSED DIRECTLY FROM THE THIRD PARTY SUPPLIER. AN AVAYA CHANNEL PARTNER'S HOSTING OF AVAYA PRODUCTS MUST BE AUTHORIZED IN WRITING BY AVAYA AND IF THOSE HOSTED PRODUCTS USE OR EMBED CERTAIN THIRD PARTY SOFTWARE, INCLUDING BUT NOT LIMITED TO MICROSOFT SOFTWARE OR CODECS, THE AVAYA CHANNEL PARTNER IS REQUIRED TO INDEPENDENTLY OBTAIN ANY APPLICABLE LICENSE AGREEMENTS, AT THE AVAYA CHANNEL PARTNER'S EXPENSE, DIRECTLY FROM THE APPLICABLE THIRD PARTY SUPPLIER.

WITH RESPECT TO CODECS, IF THE AVAYA CHANNEL PARTNER IS HOSTING ANY PRODUCTS THAT USE OR EMBED THE G.729 CODEC, H.264 CODEC, OR H.265 CODEC, THE AVAYA CHANNEL PARTNER ACKNOWLEDGES AND AGREES THE AVAYA CHANNEL PARTNER IS RESPONSIBLE FOR ANY AND ALL RELATED FEES AND/OR ROYALTIES. THE G.729 CODEC IS LICENSED BY SIPRO LAB TELECOM INC. SEE [WWW.SIPRO.COM/CONTACT.HTML](http://www.sipro.com/contact.html). THE H.264 (AVC) CODEC IS

LICENSED UNDER THE AVC PATENT PORTFOLIO LICENSE FOR THE PERSONAL USE OF A CONSUMER OR OTHER USES IN WHICH IT DOES NOT RECEIVE REMUNERATION TO: (I) ENCODE VIDEO IN COMPLIANCE WITH THE AVC STANDARD ("AVC VIDEO") AND/OR (II) DECODE AVC VIDEO THAT WAS ENCODED BY A CONSUMER ENGAGED IN A PERSONAL ACTIVITY AND/OR WAS OBTAINED FROM A VIDEO PROVIDER LICENSED TO PROVIDE AVC VIDEO. NO LICENSE IS GRANTED OR SHALL BE IMPLIED FOR ANY OTHER USE. ADDITIONAL INFORMATION FOR H.264 (AVC) AND H.265 (HEVC) CODECS MAY BE OBTAINED FROM MPEG LA, L.L.C. SEE [HTTP://WWW.MPEGLA.COM](http://www.mpegla.com).

### Compliance with Laws

You acknowledge and agree that it is Your responsibility for complying with any applicable laws and regulations, including, but not limited to laws and regulations related to call recording, data privacy, intellectual property, trade secret, fraud, and music performance rights, in the country or territory where the Avaya product is used.

### Preventing Toll Fraud

"Toll Fraud" is the unauthorized use of your telecommunications system by an unauthorized party (for example, a person who is not a corporate employee, agent, subcontractor, or is not working on your company's behalf). Be aware that there can be a risk of Toll Fraud associated with your system and that, if Toll Fraud occurs, it can result in substantial additional charges for your telecommunications services.

### Avaya Toll Fraud intervention

If You suspect that You are being victimized by Toll Fraud and You need technical assistance or support, call Technical Service Center Toll Fraud Intervention Hotline at +1-800-643-2353 for the United States and Canada. For additional support telephone numbers, see the Avaya Support website: <https://support.avaya.com> or such successor site as designated by Avaya.

### Security Vulnerabilities

Information about Avaya's security support policies can be found in the Security Policies and Support section of <https://support.avaya.com/security>.

Suspected Avaya product security vulnerabilities are handled per the Avaya Product Security Support Flow (<https://support.avaya.com/css/P8/documents/100161515>).

### Downloading Documentation

For the most current versions of Documentation, see the Avaya Support website: <https://support.avaya.com>, or such successor site as designated by Avaya.

### Contact Avaya Support

See the Avaya Support website: <https://support.avaya.com> for product or Hosted Service notices and articles, or to report a problem with your Avaya product or Hosted Service. For a list of support telephone numbers and contact addresses, go to the Avaya Support website: <https://support.avaya.com> (or such successor site as designated by Avaya), scroll to the bottom of the page, and select Contact Avaya Support.

### Regulatory Statements

#### Australia Statements

#### Handset Magnets Statement:

#### Danger:

The handset receiver contains magnetic devices that can attract small metallic objects. Care should be taken to avoid personal injury.

#### Industry Canada (IC) Statements

##### RSS Standards Statement

This device complies with Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions:

1. This device may not cause interference, and

2. This device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes:

1. L'appareil ne doit pas produire de brouillage, et
2. L'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

#### Radio Transmitter Statement

Under Industry Canada regulations, this radio transmitter may only operate using an antenna of a type and maximum (or lesser) gain approved for the transmitter by Industry Canada. To reduce potential radio interference to other users, the antenna type and its gain should be so chosen that the equivalent isotropically radiated power (EIRP) is not more than that necessary for successful communication.

Conformément à la réglementation d'Industrie Canada, le présent émetteur radio peut fonctionner avec une antenne d'un type et d'un gain maximal (ou inférieur) approuvé pour l'émetteur par Industrie Canada. Dans le but de réduire les risques de brouillage radioélectrique à l'intention des autres utilisateurs, il faut choisir le type d'antenne et son gain de sorte que la puissance isotrope rayonnée équivalente ne dépasse pas l'intensité nécessaire à l'établissement d'une communication satisfaisante.

This Class B digital apparatus complies with Canadian ICES-003.

Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.

#### Radiation Exposure Statement

This equipment complies with FCC & IC RSS102 radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

Cet équipement est conforme aux limites d'exposition aux rayonnements ISED établies pour un environnement non contrôlé. Cet équipement doit être installé et utilisé avec un minimum de 20 cm de distance entre la source de rayonnement et votre corps.

#### Japan Statements

##### Class B Statement

This is a Class B product based on the standard of the VCCI Council. If this is used near a radio or television receiver in a domestic environment, it may cause radio interference. Install and use the equipment according to the instruction manual.

この装置は、クラスB情報技術装置です。この装置は、家庭環境で使用することを目的としていますが、この装置がラジオやテレビジョン受信機に近接して使用されると、受信障害を引き起こすことがあります。

取扱説明書に従って正しい取り扱いをして下さい。 VCCI-B

#### Denan Power Cord Statement



##### Danger:

Please be careful of the following while installing the equipment:

- Please only use the connecting cables, power cord, and AC adapters shipped with the equipment or specified by Avaya to be used with the equipment. If you use any other equipment, it may cause failures, malfunctioning, or fire.
- Power cords shipped with this equipment must not be used with any other equipment. In case the above guidelines are not followed, it may lead to death or severe injury.



本製品を安全にご使用頂くため、以下のことにご注意ください。

- 接続ケーブル、電源コード、ACアダプタなどの部品は、必ず製品に同梱されております添付品または指定品をご使用ください。添付品指定品以外の部品をご使用になると故障や動作不良、火災の原因となることがあります。
- 同梱されております付属の電源コードを他の機器には使用しないでください。上記注意事項を守らないと、死亡や大怪我等など人身事故の原因となることがあります。

#### México Statement

The operation of this equipment is subject to the following two conditions:

1. It is possible that this equipment or device may not cause harmful interference, and
2. This equipment or device must accept any interference, including interference that may cause undesired operation.

La operación de este equipo está sujeta a las siguientes dos condiciones:

1. Es posible que este equipo o dispositivo no cause interferencia perjudicial y
2. Este equipo o dispositivo debe aceptar cualquier interferencia, incluyendo la que pueda causar su operación no deseada.

#### Power over Ethernet (PoE) Statement

This equipment must be connected to PoE networks without routing to the outside plant.

#### U.S. Federal Communications Commission (FCC) Statements

##### Compliance Statement

The changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

To comply with the FCC RF exposure compliance requirements, this device and its antenna must not be co-located or operating to conjunction with any other antenna or transmitter.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference, and
2. This device must accept any interference received, including interferences that may cause undesired operation.

When using IEEE 802.11a wireless LAN, this product is restricted to indoor use, due to its operation in the 5.15 to 5.25GHz frequency range. The FCC requires this product to be used indoors for the frequency range of 5.15 to 5.25GHz to reduce the potential for harmful interference to co channel mobile satellite systems. High-power radar is allocated as the primary user of the 5.25 to 5.35GHz and 5.65 to 5.85GHz bands. These radar stations can cause interference with and/or damage to this device.

##### Class B Part 15 Statement

For product available in the USA/Canada market, only channel 1~11 can be operated. Selection of other channels is not possible.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designated to provide reasonable protection against harmful interferences in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interferences to radio or television reception, which can be determined by turning the

equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

#### *Radiation Exposure Statement*

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment . This equipment should be installed and operated with minimum distance of 8 in or 20 cm between the radiator and your body. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

#### **EU Countries**

This device complies with the essential requirements and other relevant provisions of Directive 1999/5/EC. A copy of the Declaration may be obtained from <http://support.avaya.com> or Avaya Inc., 4655 Great America Parkway, Santa Clara, CA 95054–1233 USA.

#### **General Safety Warning**

- Use only the Avaya approved Limited Power Source power supplies specified for this product.
- Ensure that you:
  - Do not operate the device near water.
  - Do not use the device during a lightning storm.
  - Do not report a gas leak while in the vicinity of the leak.

#### **Trademarks**

The trademarks, logos and service marks (“Marks”) displayed in this site, the Documentation, Hosted Service(s), and product(s) provided by Avaya are the registered or unregistered Marks of Avaya, its affiliates, its licensors, its suppliers, or other third parties. Users are not permitted to use such Marks without prior written consent from Avaya or such third party which may own the Mark. Nothing contained in this site, the Documentation, Hosted Service(s) and product(s) should be construed as granting, by implication, estoppel, or otherwise, any license or right in and to the Marks without the express written permission of Avaya or the applicable third party.

Avaya is a registered trademark of Avaya Inc.

All non-Avaya trademarks are the property of their respective owners. Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.

# Contents

<b>Chapter 1: Introduction</b> .....	8
Purpose.....	8
Intended audience.....	8
<b>Chapter 2: 9600 Series IP Deskphones overview</b> .....	9
9600 Series IP Deskphones models.....	10
New in this release.....	10
Feature description.....	11
Easy to use interface.....	11
Support for diverse users.....	12
Deskphone customization.....	12
Contact center models.....	12
Support for Gigabit Ethernet.....	13
Boost employee productivity.....	13
Feature comparison of H.323-based and SIP-based models.....	13
<b>Chapter 3: Interoperability</b> .....	16
Product compatibility.....	16
<b>Chapter 4: Licensing requirements</b> .....	17
<b>Chapter 5: Performance specifications</b> .....	18
Traffic.....	18
Power.....	18
Port and switch.....	19
Software.....	20
<b>Chapter 6: Environmental specifications</b> .....	21
Hardware.....	21
Altitude and air pressure .....	24
Temperature and humidity .....	25
Physical system protection .....	26
Regulatory standards.....	29
<b>Chapter 7: Dial Plan</b> .....	30
Dial plan.....	30
Dialable characters.....	30
<b>Chapter 8: Security</b> .....	31
Security overview.....	31
SSH.....	31
TLS.....	31
VPN.....	32
Avaya SBCE .....	32
EAP-TLS.....	32
SCEP.....	32

802.1X Supplicant operation.....	33
Virus malware related attacks.....	33
JITC certification.....	33
Port utilization.....	33
<b>Chapter 9: Related resources</b> .....	<b>34</b>
Documentation.....	34
Support.....	35

# Chapter 1: Introduction

---

## Purpose

This document describes tested product characteristics and capabilities, including feature descriptions, interoperability, performance specifications, security, and licensing requirements.

---

## Intended audience

This document is intended for people who want to gain a high-level understanding of the product features, functions, capacities, and limitations.



# Chapter 2: 9600 Series IP Deskphones overview

9600 Series IP Deskphones is a series of desk handset devices that you can use for unified communication. The series leverages the enterprise IP network and eliminates the need for a separate voice network.

Avaya 9600 Series IP Deskphones offers high audio quality and customizability with low power requirements. With the high-performance models of this series that can operate in both the H.323 and the Session Initiation Protocol (SIP) environment, you can:

- Make conference calls more efficient and enhance customer interactions with high-quality audio.
- Gain access to information quickly through easy-to-read and high-resolution displays.
- Speed completion of common telephony tasks by using prompts on touch screens.
- Improve productivity with context-sensitive graphical interfaces that enhance call control and call management.
- Create a survivable, scalable infrastructure that delivers reliable performance and flexible growth as business needs change.
- Increase performance by deploying Gigabit Ethernet within your infrastructure.
- Reduce energy costs using efficient Power-over-Ethernet (PoE) including sleep mode which lowers energy consumption dramatically.

The 9600 Series IP Deskphones works with the Avaya Aura® environment to provide a flexible architecture that works with your investments and accommodates growth as your business needs change.

## Related links

[9600 Series IP Deskphones models](#) on page 10

[New in this release](#) on page 10

[Feature comparison of H.323-based and SIP-based models](#) on page 13

## 9600 Series IP Deskphones models

Deskphone model	Description
9601	The 9601 deskphone is SIP-only phone that provides a four-row monochrome display and two lines with dual red and green LEDs. The phone has a built in 10/100 Ethernet switch with a port for your personal computer or a laptop.
9608/9608G	You can use up to eight lines for the deskphone. The deskphone supports a traditional user interface and a graphical monochrome display. The 9608 has a built in 10/100 Ethernet switch, and the 9608G has an integrated Gigabit.
9611G	The 9611G has a traditional user interface and a graphical color display. You can use up to eight lines with the 9611G deskphone. The 9611G deskphone has an integrated Gigabit and a USB interface. The deskphone has a graphical color display with a white backlight.
9621G	The 9621G IP deskphone provides gigabit capability and touch screen functionality. Customers with a need for gigabit connectivity to the desktop prefer the 9621G deskphone.
9641G/9641GS	The 9641G/9641GS deskphone provides advanced capabilities with a color touch screen, wideband speaker, USB interface, Bluetooth® enabled headset support, and gigabit connectivity to the desktop. Customers who require gigabit capability for the desktop and the option to add more advanced capabilities prefer the 9641G/9641GS deskphone.

### Related links

[9600 Series IP Deskphones overview](#) on page 9

## New in this release

### Security enhancements

- Supports OpenSSL FIPS 140-2 certified cryptographic algorithms.
- Supports IPv6.
- Supports OpenSSL FIPS 140-2 certified cryptographic algorithms
- Supports Department of Defense solution deployment with Joint Inter-operability Test Command (JITC) compliance.
- Supports display of SSH fingerprint in the Administration menu.
- Displays version of OpenSSH and OpenSSL in the Administration menu.
- Supports SHA2 hash algorithm and strong encryption (256 bit symmetric and RSA 2048 and 4096 bit asymmetric keys) in TLS mode.

- Supports SRTP/SRTCP and TLS v1.2.
- Supports Enhanced Avaya Services Login (EASG) feature where an administrator can escalate to root privileges using an authentication file.

### **IPv6 and related features**

- Supports ICMPv6, PPMv6, and DHCPv6.
- SIP registration over IPv4 and IPv6.
- Supports call features and MDA devices with ANAT and non-ANAT phones.
- Supports early media, delayed media, and media reshuffling with ANAT.

### **AS-SIP features**

- Supports Multiple Level Precedence and Preemption, DSCP, and Blind Transfer as part of the AS-SIP feature.

### **Related links**

[9600 Series IP Deskphones overview](#) on page 9

---

## **Feature description**

9600 Series IP Deskphones offers the following features:

- Easy to use interface
- Support for diverse users
- Deskphone customization
- Contact center models
- Support for Gigabit Ethernet
- Boost employee productivity

---

## **Easy to use interface**

Avaya 9600 Series IP Deskphones has:

- Clear and intuitive user interface.
- Monochrome and color high resolution screens that display context sensitive information, contextual menus, prompts, and instructions that are easy to read.
- Touch screens on select models that you can use to navigate through the applications for Weather, World Clock, My Pictures, WML Browser, and Favorites.
- High resolution graphical displays.
- Integrated LED buttons that are available on traditional models 9601, 9608, 9608G and 9611G provide visual cues that enhance usability.

- Adapter interfaces that accommodate button modules and dual headset adapters to provide flexibility and adaptability. You can use SBM24 and BM12 button modules that provide up to 24 and 12 system based Call Appearances or Feature buttons.
- USB support with the H.323–based 9611G and 9641G models. These models support one USB device on the USB interface if you enable the USB power parameter through the settings file.

---

## Support for diverse users

9600 Series IP Deskphones meets the need of the following user types.

User type	Description
Walkup users	People who visit your company, such as customers or suppliers. The 9601 model is ideal for these users.
Everyday users	People who use a phone as one of many communications tools – along with IM, email, or PDA. The 9608, 9608G, 9611G, and 9621G models meet their needs.
Essential users	People who rely on real-time voice communication and make use of many advanced phone applications. The 9611 and 9621G models meet their needs.
Navigators	People who are on the phone throughout the day because they handle calls for others, such as receptionists and executive assistants. The 9641G model is ideal for these users.

---

## Deskphone customization

You can customize 9600 Series IP Deskphones through:

- Custom logos that enhances corporate identity and branding.
- Screen savers and background display images.

---

## Contact center models

Contact center versions of the 9608, 9608G, 9611G, 9621G, and 9641G models provides a range of features for enhancing agent productivity, such as handling greetings, monitoring calls in the queue, service observing for remote monitoring, updating status, and quickly completing many other day-to-day tasks. You can add a dual headset adapter to the 9608, 9608G, 9611G, and 9641G models so that you can use two headsets simultaneously. You can use a contact center faceplate on the 9641G model that eliminates the handset cradle.

---

## Support for Gigabit Ethernet

Gigabit Ethernet helps ensure compatibility with your current network and leverages existing bandwidth efficiently. Gigabit Ethernet handles data intensive traffic to co-located computers for high performance that facilitates the demands of future services and applications.

---

## Boost employee productivity

To help users, 9600 Series IP Deskphones provides:

- Collaboration features, such as conference calls, instant messaging for only SIP-based phones, and Web applications.
- Increased call control and call management with intuitive interface and context sensitive screens. Touch screen options provide easy-to-manage messages and quick access to key applications such as call logs and phone book.
- Calendar integration for only SIP-based phones through which phones can display appointments and call into conference calls with a single button press.
- Presence integration for only SIP-based phones through which phones can display presence status of other users in the phone contact list. For example, whether the other user is on a call or in a do-not-disturb mode.
- Easy-to-use critical functions, such as call transferring, call forwarding, and conference calls.

---

## Feature comparison of H.323-based and SIP-based models

Two major protocols that handle Voice over IP (VoIP) signaling for 9600 Series IP Deskphones are SIP and H.323. The two protocols provide connection control and call progress signaling, but in very different ways. You can use these protocols simultaneously over the same network. The 9600 Series IP Deskphones models do not support both protocols at the same time. Neither protocol is necessarily superior, but each offers some unique advantages.

Feature	H.323-based models	SIP-based models
Additional required servers	None	Use the following servers: <ul style="list-style-type: none"> <li>• SIP Proxy server to control SIP signalling.</li> <li>• Network Time server to control time-related parameters.</li> <li>• Presence server to track presence information of contacts added in the contacts list.</li> </ul>
Backup and restore	Use HTTP to store backup files.	Use the Personal Profile Manager (PPM) services for backup and restore.
Network Address Translation (NAT)	Support	Do not support
Settings file and system parameters	Same as used by SIP models	Same as used by H.323. However, there are number of SIP-specific parameters used only by SIP-based models.

*Table continues...*

Feature	H.323-based models	SIP-based models
Language Support	Support the following languages: <ul style="list-style-type: none"> <li>• Arabic</li> <li>• Chinese</li> <li>• Dutch</li> <li>• English</li> <li>• Canadian French</li> <li>• Parisian French</li> <li>• German</li> <li>• Hebrew</li> <li>• Italian</li> <li>• Japanese</li> <li>• Korean</li> <li>• Polish</li> <li>• Portuguese</li> <li>• Russian</li> <li>• Latin American Spanish</li> <li>• Thai</li> <li>• Turkish</li> </ul>	Support the following languages: <ul style="list-style-type: none"> <li>• Arabic</li> <li>• Simplified Chinese</li> <li>• Dutch</li> <li>• English</li> <li>• Parisian French</li> <li>• German</li> <li>• Hebrew</li> <li>• Italian</li> <li>• Japanese</li> <li>• Korean</li> <li>• Brazilian Portuguese</li> <li>• Russian</li> <li>• Latin American Spanish</li> <li>• Canadian French</li> <li>• Castilian Spanish</li> </ul>
Resource ReSerVation Protocol (RSVP)	Support	Do not support
Quality of Service (QoS)	Use Avaya Aura <sup>®</sup> Communication Manager to set QoS.	Use parameters, such as L2QAUD, L2QSIG, DSCPAUD, and DSCPSIG to set QoS.
Presence and Instant Message	Do not support	Support
Integration with Microsoft Exchange and calender	Do not support	Support
Support of remote workers	Through Virtual Private Network (VPN)	Through Avaya SBCE (Session Border Controller for Enterprise)
Integrated Bluetooth on 9641G and 9641GS	Support	Support

### Related links

[9600 Series IP Deskphones overview](#) on page 9

# Chapter 3: Interoperability

---

## Product compatibility

For the latest and most accurate product compatibility information of 9600 Series IP Deskphones, see [Product Compatibility Matrix](#).

For the latest and most accurate compatibility information of SIP-based 9600 Series IP Deskphones with headsets, see the document *Avaya one-X® 96X1 Series IP Deskphone Headset Profiles* at the [Avaya Support](#) website.



# Chapter 4: Licensing requirements

You require the following licences for 9600 Series IP Deskphones:

- The Right to Use the software that runs on 9600 Series IP Deskphones. This license is already included with the purchase of the deskphone.
- The Right to Connect 9600 Series IP Deskphones to Communication Manager, Session Manager, or IP Office. This license is controlled by simultaneous user licenses that these servers enforce.

You can purchase licenses in bulk as required. For more information on the software license terms, see [Policies & Legal](#).

# Chapter 5: Performance specifications

---

## Traffic

9600 Series IP Deskphones supports operations that IEEE 802.3 standards specify. The following table lists the standards and the models that support them.

Standard	9601	9608 9608G	9611G	9621G	9641G	9641 GS
10BASE-T with autonegotiation	Yes	Yes	Yes	Yes	Yes	Yes
100BASE-TX with autonegotiation	Yes	Yes	Yes	Yes	Yes	Yes
1000BASE-T with autonegotiation	No	9608: No 9608G: Yes	Yes	Yes	Yes	Yes
Internal Ethernet switch that support half-duplex or full-duplex at the speed of 10 Mbps or 100 Mbps for non-gigabit phones and 10 Mbps, 100 Mbps, or 1000 Mbps for gigabit phones on either interface	Yes	Yes	Yes	Yes	Yes	Yes
Media Access Control (MAC) frame structure	Yes	Yes	Yes	Yes	Yes	Yes
Collision backoff delay	Yes	Yes	Yes	Yes	Yes	Yes
Auto MDI/MDI-X	Yes	Yes	Yes	Yes	Yes	Yes

---

## Power

9600 Series IP Deskphones supports:

- Local powering, that is, by plugging the power cord into the power source.
- Power over Ethernet (PoE) or LAN-based powering as per IEEE 802.3af specification.

The IEEE 802.3af standard specifies up to 15.4 W of DC power that has a voltage of minimum 44 V DC and a current specification of 350 mA for each device. The following table provides the details of power consumption for each model.

Standard	9601	9608 9608G	9611G	9621G	9641G	9641G S
IEEE power classification	1	1	1	2	2	1: When the switch is in the low position .  3: When the switch is in the high position .
Power consumption when conservation mode is disabled (watts)	1.73	2.08	3.12	3.49	3.44	2.40
Power usage when conservation mode is enabled and backlight is turned off (watts)	1.73	1.93	2.64	3.18	3.28	3.55
Maximum power consumption (watts)	2.02	2.55	3.78	4.27	4.12	4.50
Power class target when button module is attached	Does not support button module	1,2	1,3	Does not support button module	2,3	2,3
Power class switch to change power class when you attach button module	No	Yes	Yes	No	Yes	Yes

## Port and switch

9600 Series IP Deskphones supports the following ports and switches.

Port and switch	9601	9608 9608G	9611G	9621G	9641G	9641GS
USB 2.0	No	No	Yes	No	Yes	Yes
PC port	Yes	Yes	Yes	Yes	Yes	Yes
Headset jack	Yes	Yes	Yes	Yes	Yes	Yes
Button module interface	No	Yes	Yes	No	Yes	Yes

*Table continues...*

Port and switch	9601	9608 9608G	9611G	9621G	9641G	9641GS
Adapter interface	No	No	No	No	No	No
Ethernet interface	10/100 Mbps	9608: 10/100 Mbps  9608G: 10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps
Secondary Ethernet interface	10/100 Mbps	9608: 10/100 Mbps  9608G: 10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps
IEEE power switch	No	No	Yes	No	Yes	Yes

## Software

9600 Series IP Deskphones supports the following software.

Software	9601	9608 9608G	9611G	9621G	9641G	9641GS
Call control protocol	SIP	SIP and H.323	SIP and H.323	SIP and H.323	SIP and H.323	SIP and H.323
Codec	<ul style="list-style-type: none"> <li>• G.711 u/a law</li> <li>• G.722</li> <li>• G.726</li> <li>• G.729 a/b</li> </ul>	<ul style="list-style-type: none"> <li>• G.711 u/a law</li> <li>• G.722</li> <li>• G.726</li> <li>• G.729 a/b</li> </ul>	<ul style="list-style-type: none"> <li>• G.711 u/a law</li> <li>• G.722</li> <li>• G.726</li> <li>• G.729 a/b</li> </ul>	<ul style="list-style-type: none"> <li>• G.711 u/a law</li> <li>• G.722</li> <li>• G.726</li> <li>• G.729 a/b</li> </ul>	<ul style="list-style-type: none"> <li>• G.711 u/a law</li> <li>• G.722</li> <li>• G.726</li> <li>• G.729 a/b</li> </ul>	<ul style="list-style-type: none"> <li>• G.711 u/a law</li> <li>• G.722</li> <li>• G.726</li> <li>• G.729 a/b</li> </ul>

# Chapter 6: Environmental specifications

## Hardware

9600 Series IP Deskphones supports the following hardware specifications.

Standard	9601	9608 9608G	9611G	9621G	9641G	9641GS
Dimensions in inches (cms):	9.1 (23)	9.1 (23)	9.1 (23)	9.1 (23)	9.1 (23)	9.1 (23)
Height	7.1 (18)	8 (20.4)	8 (20.4)	9.1 (23)	9.1 (23)	9.1 (23)
Width	1.4 (3.5)	1.4 (3.5)	1.4 (3.5)	1.4 (3.5)	1.4 (3.5)	1.4 (3.5)
Depth without the stand						
Wall mountable	Yes	Yes	Yes	Yes	Yes	Yes
Stand	Dual position	Dual position flip	Dual position flip	Dual position flip	Dual position flip	Dual position flip
Touch screen	NA	NA	NA	Resistive	Resistive	Capacitive
Display type	Monochrome	FSTN monochrome	TFT 8 bit color	TFT 24 bit color	TFT 24 bit color	TFT 24 bit color
Display size in inches (cms)	2.4 x 1.1 (6.2 x 2.6)	3.2 x 2.2 (8.2 x 5.5)	2.8 x 2.1 (7.0 x 5.3)	3.7 x 2.1 (9.5 x 5.4)	4.1 x 2.3 (10.4 x 5.9)	4.1 x 2.3 (10.4 x 5.9)
Display resolution	132 x 59 pixel	180 x 120 pixel	320 x 240 pixel	480 x 272 pixel	480 x 272 pixel	480 x 272 pixel
Display backlight	No backlight	White	Yes	Yes	Yes	Yes
Call appearance or display buttons	2 with red and green LEDs each	8 with red and green LEDs each	8 with red and green LEDs each	Integrated in display	Integrated in display	Integrated in display
Softkeys call control	3	4	4	Variable integrated in display	Variable integrated in display	Variable integrated in display

*Table continues...*

Environmental specifications

<b>Standard</b>	<b>9601</b>	<b>9608 9608G</b>	<b>9611G</b>	<b>9621G</b>	<b>9641G</b>	<b>9641GS</b>
Bluetooth support	No	No	No	No	Integrated Bluetooth supported	Integrated Bluetooth supported
Handset	Wideband	Wideband	Wideband	Wideband	Wideband	Wideband
Handset weight in lbs (gms)	0.31(141)	0.31 (141)	0.31 (141)	0.31 (141)	0.31 (141)	0.31 (141)
Handset cord: length, type	9 ft (274.3 cms), 4-conductor coiled	9 ft (274.3 cm), 4-conductor coiled	9 ft (274.3 cm), 4-conductor coiled	9 ft (274.3 cm), 4-conductor coiled	9 ft (274.3 cm), 4-conductor coiled	9 ft (274.3 cm), 4-conductor coiled
Handset transmission frequency	7 Khz	7 Khz	7 Khz	7 Khz	7 Khz	7 Khz
Handset receiving frequency	7 Khz	7 Khz	7 Khz	7 Khz	7 Khz	7 Khz
Handsfree	Narrowband	Narrowband	Narrowband	Wideband	Wideband	Wideband
Microphone	1 omni-directional	1 omni-directional	1 omni-directional	1 omni-directional	1 omni-directional	1 omni-directional
Gigabit Ethernet	No	9608: No 9608G: Yes	Yes	Yes	Yes	Yes
Ethernet signal range	100 meters on category 5e unshielded twisted pair (UTP) cabl	100 meters on category 5e unshielded twisted pair (UTP) cable	100 meters on category 5e unshielded twisted pair (UTP) cable	100 meters on category 5e unshielded twisted pair (UTP) cable	100 meters on category 5e unshielded twisted pair (UTP) cable	100 meters on category 5e unshielded twisted pair (UTP) cable

*Table continues...*

Standard	9601	9608 9608G	9611G	9621G	9641G	9641GS
Buttons	<p>Activation force = 100 to 160 grams</p> <p>Travel distance = 1.1 to 1.3 millimeters</p> <p>Height = approximately 0.5 millimeter above the housing when fully depressed</p> <p>Snap ratio of 0.35 +/- 0.1 or higher</p>	<p>Activation force = 100 to 160 grams</p> <p>Travel distance = 1.1 to 1.3 millimeters</p> <p>Height = approximately 0.5 millimeter above the housing when fully depressed</p> <p>Snap ratio of 0.35 +/- 0.1 or higher</p>	<p>Activation force = 100 to 160 grams</p> <p>Travel distance = 1.1 to 1.3 millimeters</p> <p>Height = approximately 0.5 millimeter above the housing when fully depressed</p> <p>Snap ratio of 0.35 +/- 0.1 or higher</p>	<p>Activation force = 100 to 160 grams</p> <p>Travel distance = 1.1 to 1.3 millimeters</p> <p>Height = approximately 0.5 millimeter above the housing when fully depressed</p> <p>Snap ratio of 0.35 +/- 0.1 or higher</p>	<p>Activation force = 100 to 160 grams</p> <p>Travel distance = 1.1 to 1.3 millimeters</p> <p>Height = approximately 0.5 millimeter above the housing when fully depressed</p> <p>Snap ratio of 0.35 +/- 0.1 or higher</p>	<p>Activation force = 100 to 160 grams</p> <p>Travel distance = 1.1 to 1.3 millimeters</p> <p>Height = approximately 0.5 millimeter above the housing when fully depressed</p> <p>Snap ratio of 0.35 +/- 0.1 or higher</p>

*Table continues...*

Standard	9601	9608 9608G	9611G	9621G	9641G	9641GS
Permanently labeled feature buttons	Speaker with red LED Headset with red LED Mute with red LED Volume Phone History with red LED Contacts “A” Menu Message Navigation: up, down, left, right OK More	Speaker with red LED Headset with red LED Mute with red LED Volume Phone History with red LED Contacts “A” Home Message Navigation: up, down, left, right OK	Speaker with red LED Headset with red LED Mute with red LED Volume Phone History with red LED Contacts “A” Home Message Navigation: up, down, left, right OK	Speaker with red LED Headset with red LED Mute with red LED Volume Phone History with red LED Contacts “A” Home Message with red LED Forwarding with red LED	Speaker with red LED Headset with red LED Mute with red LED Volume Phone History with red LED Contacts “A” Home Message with red LED Forwarding with red LED	Speaker with red LED Headset with red LED Mute with red LED Volume Phone History with red LED Contacts “A” Home Message with red LED Forwarding with red LED
Reliability rate in technician usage rate measured as the number of units used from repair stock per month per 100 units in the installed base	Less than or equal to 0.1	Less than or equal to 0.1	Less than or equal to 0.1	Less than or equal to 0.1	Less than or equal to 0.1	Less than or equal to 0.1

## Altitude and air pressure

9600 Series IP Deskphones function normally at altitudes from sea level to 10,000 feet and can withstand a pressure of 15.2 to 9.4 psia.



---

# Temperature and humidity

All Avaya IP 9600 Series IP deskphones work in a temperature range from 40 to 120 degrees Fahrenheit or 4 to 49 degrees Celsius.

## Storage environment specifications

**Extreme temperature specifications:** All Avaya IP 9600 Series IP deskphones work normally after being soaked for at least 6 hours each in a non-operational state at -40 degree Fahrenheit and any relative humidity, at 90 degree Fahrenheit and 90% relative humidity, and at 150 degrees Fahrenheit and 15% relative humidity. The deskphones can function normally after up to three hours of recovery time at ambient conditions following each stress.

**Temperature and humidity specifications:** All Avaya IP 9600 Series IP deskphones function normally after a recovery time of up to three hours at ambient conditions when cycled through the following temperature and non-condensing humidity conditions three times: 30 minutes at 150 degree Fahrenheit and 15 percent relative humidity, followed by 30 minutes at 90 degrees Fahrenheit and 90 percent relative humidity, followed by 30 minutes at -40 degrees F and any convenient humidity.

**Normal operating specification:** All Avaya IP 9600 Series IP deskphones function normally in the environment where temperatures are between 40 degrees Fahrenheit and relative humidities are between 5 percent and 95 percent, except that above 84 degree Fahrenheit, the maximum relative humidity is limited to that corresponding to a specific (absolute) humidity of 168 grains of water vapor per pound (lbm) of dry air. For example, 34 percent relative humidity at 120 degrees Fahrenheit, assuming an atmospheric pressure of 14.7 psia. The deskphones are allowed up to 30 minutes to stabilize at each temperature tested.

## Design for Environment Guidelines and specifications

All 9600 Series IP deskphones conform to the Design for Environment Guidelines and Requirements [8.1-5] as clarified below.

DFE Guidelines for Energy Efficient Products (Section 2): All 9600 Series IP deskphones do not require a cooling fan.

DFE Guidelines for Products Containing Batteries (Section 3): All 9600 Series IP deskphones do not contain batteries.

DFE Guidelines for Designing Plastic Parts (Section 4): All 9600 Series deskphone plastic parts are not coated (Section 4.4). Note: Section 4.4 of the Design for Environment Guidelines and Requirements specifies that plastic parts are not to be painted. However some deskphones might have been painted.

All 9600 Series IP deskphones housing and handset surfaces are textured (Section 4.5).

All 9600 Series deskphone plastic parts do not use resins containing:

- PVC (Section 4.7.1.2)
- Brominated flame retardants: polybrominated biphenyl, polybrominated biphenyl oxide (PBBO, also called polybrominated biphenyl ether (PBBE), polybrominated diphenyl oxide (PBDO) and polybrominated diphenyl ether (PBDE)), bromomethane and halothane (Sections 4.7.1.3, 4.9.1 and Appendix A)
- Halogenated flame retardants (Section 4.9.2)

- Heavy metal additives: lead, cadmium, chromium and mercury (Sections 4.7.1.4 and 4.9.3).
- All 9600 Series IP deskphone plastic parts weighing more than 25 grams are marked with ISO-compliant resin codes (Section 4.8). DFE Guidelines for Designing Printed Wiring Boards (Section 5):
- All 9600 Series IP deskphones do not contain lead (Section 5.3). All IP telephones do not use components containing mercury (Section 5.7.2).
- DFE Guideline for Waste Electrical and Electronic Equipment (WEEE) (Section 6.5.1). See also section [8.4-6].

## Physical system protection

### External voltages, surges, and transient specifications

All Avaya 9600 Series IP deskphones function normally after being subjected to surges marked normal in the table below. All Avaya 9600 Series IP deskphones comply with appropriate safety requirements after being subjected to all surges in the following table. Surges are specified below as either normal or FCC (Part 68 Rules). The peak voltage and peak current define a constant source resistance of the surge generator.

**Table 1: High voltage surge table**

TYPE	Peak voltage (Volts)	Peak current (Amps)	Maximum rise time (µ sec)	Maximum decay time (µ sec)	Number of surges of polarity each
P-2 FCC	2500	1000	2	10	10
P-4A Normal	6000	200	0.5	See Note A	12
T-1A Normal	6000	200	0.5	See Note A	12

NOTE A: 0.5 µsec - 100 kHz ringing wave shape; refer to IEEE-587 IEEE, Inc., IEEE Guide for Surge Voltages in Low-Voltage AC Power Circuits, IEEE Std 587-1980, January 30, 1981.

Peak voltage applies with the source terminated in at least 10,000 Ohms. Peak current applies with the source terminated in a short circuit. Rise and decay times apply to both voltage and current waveforms terminated as indicated above, and are defined as follows: Rise Time is the interval between the 10 percent and 90 percent of peak points on the leading edge multiplied by 1.25.

Decay Time is the time interval between the 10 percent of peak point on the leading edge and the 50 percent of peak point on the trailing edge.

### Electromagnetic compatibility specifications

Radiated Emissions: All 9600 Series IP deskphones meet the applicable FCC Rules Part 15 regulations for Class B devices. Radiated emissions from 9600 Series IP deskphones do not exceed the level of field strength specified in the following table for Class B devices.

**Table 2: Maximum allowed radiated field strength**

Freq	Class A		Class B
	Field strength in dB $\mu$ V/m	Field strength in dB $\mu$ V/m	
	At 10 metres	At 3 metres	At 3 metres
30 to 88	39	49	40
88 to 216	44	54	43
216 to 960	46	56	46
above 960	50	60	54

### Radiated RF emission specification

All 9600 Series IP deskphones meet Class B radiated emissions limits EN55022:2006 as specified in the following table:

**Table 3: Radiated Emission Limits for International Applications**

Frequency	Class A	Class B
	Quasi-Peak Field Strength Limit (dB $\mu$ V/m at 10 m)	Quasi-Peak Field Strength Limit (dB $\mu$ V/m at 10 m)
30 - 230	40	30
230 - 1000	47	37

### Conducted RF emissions specifications (FCC)

All 9600 Series IP deskphones meet the applicable FCC Rules Part 15 regulations <sup>2</sup> for Class B devices. 9600 Series IP deskphones limit radio frequency voltage conducted back into the ac power lines to values below FCC Part 15 Class B levels.

### Conducted RF emissions specifications (CE Mark)

All 9600 Series IP deskphones meet the following Class B conducted emissions limits for ac Mains and for telecommunication ports (EN55022:2006).

**Table 4: Conducted Emissions Limits for International Applications on AC Mains**

Freq (MHz)	Class A Emission Limits (dB $\mu$ V)		Class B Emission Limits (dB $\mu$ V)	
	Quasi-Peak	Average	Quasi-Peak	Average
0.15 – 0.5	79	66	66 - 56	56 - 46
0.5 - 5	73	60	56	46
5 - 30	73	60	60	50

**Table 5: Conducted Common Mode Emissions Limits for International Applications on Telecommunication Ports for Class B Equipment**

Freq (MHz)	Voltage limits (db $\mu$ V)		Voltage limits (db $\mu$ A)	
	Quasi-Peak	Average	Quasi-Peak	Average
0.15 – 0.5	84 - 74	74 - 64	40 - 30	30 - 20
0.5 - 30	74	64	30	20

Where a range of limits is specified, the limits decrease linearly with the logarithm of the frequency. The above limits are given in terms of the current measured into a terminating impedance stabilization network (ISN) under the assumption that the 150-Ohm impedance will be realized throughout the test range. The tighter (lower) limit applies at the transition frequency.

**Electrostatic Discharge (ESD) Immunity – ESD Performance under Normal Operation for CE Mark:**

All 9600 Series IP deskphones comply with the ESD immunity requirements in EN 55024:1998, and Amendment A1:2001 to EN 55024:1998 and Amendment A2:2003 to EN 55024:1998

**Radiated RF Electromagnetic Field Immunity**

All 9600 Series IP deskphones comply with the conducted RF Field immunity requirements in EN 55024:1998, and Amendment A1:2001 to EN 55024:1998 and Amendment A2:2003 to EN 55024:1998, including the particular test conditions and particular performance criteria in Appendix A of that standard.

**EFT Immunity for CE Mark**

All 9600 Series IP deskphones comply with the EFT immunity requirements in EN 55024:1998, and Amendment A1:2001 to EN 55024:1998 and Amendment A2:2003 to EN 55024:1998.

**Surge Immunity for CE Mark**

All 9600 Series IP deskphones comply with the Surge immunity requirements in EN 55024:1998, and Amendment A1:2001 to EN 55024:1998 and Amendment A2:2003 to EN 55024:1998.

**Power Frequency Magnetic Field Immunity for CE Mark**

All 9600 Series IP deskphones comply with the Power Frequency Magnetic Field immunity requirements in EN 55024:1998, and Amendment A1:2001 to EN 55024:1998 and Amendment A2:2003 to EN 55024:1998, including the particular test conditions and particular performance criteria in Appendix B of that standard.

**AC Voltage Dips and Interruptions Immunity for CE Mark**

All 9600 Series IP deskphones comply with the ac Voltage Dips and Interruptions immunity requirements in EN 55024:1998, and Amendment A1:2001 to EN 55024:1998 and Amendment A2:2003 to EN 55024:1998.

**Safety and Protection Platform specifications**


All 9600 Series IP deskphones conform to the requirements of IEC-60950-1 [8.4-4a], EN60950-1 [8.4-4b] and UL-60950-1 [8.4-4c].

All 9600 Series IP deskphones are listed with c/UL to the requirements of UL 60950-1.

All 9600 Series IP deskphones are certified to the requirements of IEC 60950-1 according to the procedure of the IECEE CB Scheme.

## Regulatory standards

**Table 6: Telecom specifications**

US FCC (Part 15, including Class B EMC, and Part 68 (HAC) hearing-aid compatibility)
European Union CE (including Class B EMC and CB Scheme report with all National Differences) EC EN55022: 2006
CSA / UL (Canadian and USA Safety)
VCCI (Japanese Voluntary Control Council for Interference by Information Technology Equipment)
CB Test for TUV
JATE (Japan Approvals Institute for Telecommunications Equipment)
NOM (Normas Oficiales Mexicanas –safety)
RoHS/lead free compliance
ANATEL (label with registration number and EAN number/bar code for Brazil)
China RoHS
Korea (only MIC Information device test certificate, the Telecommunication will be done by Avaya)
AUS C-Tick
Russian PCT Type Approval
WEEE compliance with associated icon: 
FCC Part 15 Class B and EU Class B EMC requirements
ACP systems (of which the IP telephones are a part) are registered for FCC Part 68 compliance.
Dialpad layout- ITU-T Recommendation E.161 [8.6-1]
HAC on handset “HAC” is included on the phone per FCC Part 68.300 (c) to indicate hearing-aid compatibility

# Chapter 7: Dial Plan

---

## Dial plan

You can create a dial plan for 9600 Series IP Deskphones using the following characters.

Character	Description
Digits 0 through 9	Specific dialpad digits.
Asterisk (*)	The dialpad character asterisk (*).
Pound (#)	The dialpad character #, but only if it is the first character in the dialed string.
x	Any dialpad digit from 0 to 9.
Z or z	Present dial tone to the user. For example, for Feature Access Code (FAC) entry.
Brackets ([ ])	Any one character within the brackets is a valid match for a dial plan string.
Minus (-)	Any one digit between the bounds within the brackets, inclusive, is a match.
Plus (+)	The character before plus (+) may be repeated 0 or more additional times, for a valid match.
Pipe ( )	If there are multiple valid dial plan elements, each one is separated from the next by an OR symbol.
(" ")	If the dial plan text string begins or ends with an OR symbol, that symbol is ignored.

---

## Dialable characters

Characters that a user would put in a dial string. These are different from the dial plan elements.

Character	Description
Comma (,)	A comma (,) creates a 1.5-second pause between the digits that are sent. Do not use a comma (,) as the first character in the string.
Pound (#)	Can either be the first dialed element used in a FAC or TAC or the last character which is an end of dial string indication.
Asterisk (*)	Can either be the 1st dialed element used in a FAC or TAC.

# Chapter 8: Security

---

## Security overview

9600 Series IP Deskphones support the following security features:

- HTTP authentication for backup and restore operations.
- 256-bit Advanced Encryption Standard (AES-256) media encryption.
- Supports FIPS 140-2 cryptographic algorithms for application, processes, and users.
- Supports control to switch between FIPS and non-FIPS mode.
- Supports Public Key Infrastructure (PKI) for users that use third-party certificates for all Avaya services including database.
- Supports On Line Certificate Status Protocol (OCSP) for certificate revocation.
- Supports SRTP/SRTCP and TLS v1.2.
- Secure call indicator provided by Avaya Aura® Platform 7.0.
- Compliance with IETF RFC 1948 *Defending Against Sequence Number Attacks, May 1996, 14 by S. Bellovin* .
- Support Transport Layer Security (TLS) to establish a secure connection to an HTTP server on which the upgrade and settings files reside.

---

## SSH

Avaya Services uses Secure Shell (SSH) protocol to remotely connect to 9600 Series IP Deskphones to monitor, diagnose, or debug phone performance. The 9600 Series IP Deskphones support SSHv2 only. SSHv1 is disabled.

---

## TLS

9600 Series IP Deskphones supports Transport Layer Security (TLS) to enhance the security of your HTTP environment. The deskphones support HTTP and HTTPS authentication for backup and restore operations.

## VPN

You can use H.323–based 9600 Series IP Deskphones on a Virtual Private Network (VPN) if your administrator configures the VPN option for your deskphones. VPN uses a high-speed connection to the Internet and then to the VPN-administered solution in the enterprise network. VPN provides a significant improvement of the communications capabilities of SOHO users. With the 9600 Series IP Deskphones, you can implement a VPN in enterprise networks with third-party devices.

---

## Avaya SBCE

You can use 9600 Series IP Deskphones SIP with Avaya Session Border Controller for Enterprise (SBCE) to provide support for remote workers. The SBCE gives remotely located SIP users access to the internal enterprise Unified Communications (UC) network by implementing comprehensive UC security features. These features include sophisticated firewall/NAT traversal, encryption, user authentication, and session and endpoint call policy enforcement.

---

## EAP-TLS

9600 Series IP Deskphones supports Extensible Authentication Protocol-Transport Layer Security (EAP-TLS) mode of authentication. The call server supports EAP-TLS as specified in RFC 2716 if an identity certificate is present in the deskphone.

---

## SCEP

9600 Series IP Deskphones supports Simple Certificate Enrollment Protocol (SCEP) to provide an identity certificate for use with certificate-based VPN authentication methods. The 802.1x EAP-TLS method also uses the identity certificate for authentication. When you use TLS with HTTPS, you can use the identity certificate to:

- Authenticate the deskphone
- Save the agent greetings
- Perform a backup or restore

9600 Series IP Deskphones supports Media Encryption (SRTP) and uses built-in Avaya certificates for trust management. You can apply SCEP to your VPN operations or to standard enterprise network operations.



---

## 802.1X Supplicant operation

9600 Series IP Deskphones supports Supplicant operation and Extensible Authentication Protocol (EAP), but for software Release 6.1 and earlier, only with the MD5-Challenge authentication method.

---

## Virus malware related attacks

Deskphones are delivered free from known viruses, worms, and other malware. Products are built in an environment that is free from known viruses, worms, and other malware. The "gold" version of a product is built on a machine that is known to be clean. For example, built from a known source or the operating system version is taken from the manufacturer's source.

---

## JITC certification

For products sold into the U.S. and Canadian Government and sector, Joint Interoperability Test Command (JITC) certification is a mandatory requirement. Based on the operating system and the capabilities of the product, each product must adhere to the respective standard specified at <http://iase.disa.mil/stigs/checklist/index.html>.

Verification of JITC functionality includes execution of the scripts for the respective operating system on the product. The scripts are specified at <http://iase.disa.mil/stigs/SRR/index.html>.

---

## Port utilization

For the latest and most accurate information about ports and protocols that 9600 Series IP Deskphones utilizes, see [Port Matrix](#). On the Web page, select the required link under Avaya one-X<sup>®</sup> Deskphone.

# Chapter 9: Related resources

## Documentation

See the following related documents.

Title	Use this document to:	Audience
Implementing — H.323		
Avaya deskphone H.323, 9608, 9611, 9621G, and 9641G Installation and Maintenance Guide	See install and upgrade procedures for 9601, 9608, 9611G, 9621G, and 9641G IP Deskphones in an H.323 environment.	Administrators and network engineers
Implementing — SIP		
Installing and Maintaining Avaya 9601/9608/9608G/9611G/9621G/9641G IP Deskphones SIP	See install and upgrade procedures for 9601, 9608, 9611G, 9621G, and 9641G IP Deskphones in a SIP environment.	Administrators and network engineers
Using — H.323		
Using Avaya IP Deskphone H.323 9608 and 9611G	See tasks that you can perform using the Avaya IP Deskphone H.323 9608 and 9611G deskphone.	Users and administrators
Using Avaya IP Deskphone H.323 9621G and 9641G	See tasks that you can perform using the Avaya IP Deskphone H.323 9621G and 9641G deskphone.	Users and administrators
Using Avaya IP Deskphone H.323 9608, 9611G, 9621G and 9641G in the Call Center	See tasks that you can perform in a call center using the Avaya IP Deskphone H.323 9608, 9611G, 9621G, and 9641G deskphone.	Users and administrators
Administering Avaya IP Deskphone H.323, 9608, 9611G, 9621G, and 9641G	Administer configurations and settings for 9608, 9611G, 9621G, and 9641G IP deskphones in an H.323 environment.	Administrators
Using — SIP		
Using Avaya 9601 IP Deskphone SIP	See the capabilities of a 9601 IP SIP deskphone and to learn about how various features work.	Users and administrators
Using Avaya 9608/9608G/9611G IP Deskphones SIP	See the capabilities of 9608 and 9611G IP SIP deskphones and to learn about how various features work.	Users and administrators

*Table continues...*

Title	Use this document to:	Audience
Using Avaya 9621G/9641G IP Deskphones SIP	See the capabilities of 9621G and 9641G IP SIP deskphones and to learn about how various features work.	Users and administrators
Using Avaya 9608/9608G/9611G IP Deskphones SIP for Call Center Agents	See the capabilities of 9608 and 9611G IP SIP deskphones in a call center set up and to learn about how various features work.	Call center agents and administrators
Using Avaya 9621G/9641G IP Deskphones SIP for Call Center Agents	See the capabilities of 9621G and 9641G IP SIP deskphones in a call center set up and to learn about how various features work.	Call center agents and administrators
Avaya 9601 IP Deskphones SIP Quick Reference	See frequently used tasks.	Users and administrators
Avaya 9608/9608G/9611G IP Deskphones SIP Quick Reference	See frequently used tasks.	Users and administrators
Avaya 9621G/9641G IP Deskphones SIP Quick Reference	See frequently used tasks.	Users and administrators
Avaya 9608/9608G/9611G/9621G/9641G IP Deskphones SIP Quick Reference for Call Center Agents	See frequently used tasks.	Call center agents and administrators
Administering 9601/9608/9608G/9611G/9621G/9641G IP Deskphones SIP	Administer configurations and settings for 9608, 9611G, 9621G, and 9641G IP deskphones in a SIP environment.	Administrators

---

## Support

Go to the Avaya Support website at <http://support.avaya.com> for the most up-to-date documentation, product notices, and knowledge articles. You can also search for release notes, downloads, and resolutions to issues. Use the online service request system to create a service request. Chat with live agents to get answers to questions, or request an agent to connect you to a support team if an issue requires additional expertise.

# Index

## Numerics

100BASE-T .....	<a href="#">18</a>
100BASE-TX .....	<a href="#">18</a>
10BASE-T .....	<a href="#">18</a>
802.1X Supplicant operation .....	<a href="#">33</a>

## A

Altitude and air pressure specification .....	<a href="#">24</a>
auto MDI/MDI-X .....	<a href="#">18</a>
autonegotiation .....	<a href="#">18</a>

## C

call control protocol .....	<a href="#">20</a>
codec .....	<a href="#">20</a>
Collision backoff delay .....	<a href="#">18</a>
compatibility matrix .....	<a href="#">16</a>
compatible headsets .....	<a href="#">16</a>
compatible products .....	<a href="#">16</a>
contact center models .....	<a href="#">12</a>

## D

deskphone customization .....	<a href="#">12</a>
dialable characters .....	<a href="#">30</a>
dial plan specification .....	<a href="#">30</a>
difference between H.323 and SIP models .....	<a href="#">13</a>

## E

EAP-TLS .....	<a href="#">32</a>
employee productivity .....	<a href="#">13</a>
enhancements, new in this release .....	<a href="#">10</a>
essential users .....	<a href="#">12</a>
everyday users .....	<a href="#">12</a>
Extensible Authentication Protocol-Transport Layer Security .....	<a href="#">32</a>

## F

feature comparison .....	<a href="#">13</a>
features .....	<a href="#">11</a>
boost employee productivity .....	<a href="#">13</a>
contact center models .....	<a href="#">12</a>
deskphone customization .....	<a href="#">12</a>
diverse users .....	<a href="#">12</a>
easy to use interface .....	<a href="#">11</a>
Gigabit support .....	<a href="#">13</a>

## G

Gigabit support .....	<a href="#">13</a>
-----------------------	--------------------

## H

handset	
cord .....	<a href="#">21</a>
receiving frequency .....	<a href="#">21</a>
transmission frequency .....	<a href="#">21</a>
weight .....	<a href="#">21</a>
hardware	
backlight .....	<a href="#">21</a>
bluetooth .....	<a href="#">21</a>
buttons .....	<a href="#">21</a>
call appearance .....	<a href="#">21</a>
dimensions	
stand .....	<a href="#">21</a>
wall mountable .....	<a href="#">21</a>
Gigabit Ethernet .....	<a href="#">21</a>
handset .....	<a href="#">21</a>
handsfree .....	<a href="#">21</a>
microphone .....	<a href="#">21</a>
PCB .....	<a href="#">21</a>
softkeys .....	<a href="#">21</a>
touch screen .....	<a href="#">21</a>
hardware specification .....	<a href="#">21</a>
headset compatibility .....	<a href="#">16</a>

## I

internal Ethernet switch .....	<a href="#">18</a>
--------------------------------	--------------------

## J

Joint Interoperability Test Command certification .....	<a href="#">33</a>
---	--------------------

## L

legal notices .....	
legal requirements .....	<a href="#">17</a>
licensing requirements .....	<a href="#">17</a>

## M

MAC frame structure .....	<a href="#">18</a>
models .....	<a href="#">10</a>

## N

navigators .....	<a href="#">12</a>
------------------	--------------------

<b>O</b>	
overview .....	<a href="#">9</a>
security .....	<a href="#">31</a>
<b>P</b>	
physical system protection specification .....	<a href="#">26</a>
policies .....	<a href="#">17</a>
port and switch	
adapter interface .....	<a href="#">19</a>
button module .....	<a href="#">19</a>
Ethernet interface .....	<a href="#">19</a>
Gigabit Ethernet switch .....	<a href="#">19</a>
headset jack .....	<a href="#">19</a>
IEEE power switch .....	<a href="#">19</a>
PC port .....	<a href="#">19</a>
secondary interface .....	<a href="#">19</a>
USB .....	<a href="#">19</a>
port and switch specification .....	<a href="#">19</a>
port utilization .....	<a href="#">33</a>
power	
classification .....	<a href="#">18</a>
class target .....	<a href="#">18</a>
usage .....	<a href="#">18</a>
power specification .....	<a href="#">18</a>
product compatibility .....	<a href="#">16</a>
product compatibility matrix .....	<a href="#">16</a>
<b>R</b>	
regulatory standards .....	<a href="#">29</a>
related documentation .....	<a href="#">34</a>
requirement	
licensing .....	<a href="#">17</a>
right to connect .....	<a href="#">17</a>
right to use .....	<a href="#">17</a>
<b>S</b>	
Secure Shell .....	<a href="#">31</a>
security	
802.1X Supplicant operation .....	<a href="#">33</a>
Avaya SBCE .....	<a href="#">32</a>
JITC certification .....	<a href="#">33</a>
Simple Certificate Enrollment Protocol .....	<a href="#">32</a>
SSH .....	<a href="#">31</a>
TLS .....	<a href="#">31</a>
Virus malware related attacks .....	<a href="#">33</a>
VPN .....	<a href="#">32</a>
securityEAP-TLS .....	<a href="#">32</a>
security overview .....	<a href="#">31</a>
Simple Certificate Enrollment Protocol .....	<a href="#">32</a>
software specification .....	<a href="#">20</a>
specifications	
altitude and air pressure .....	<a href="#">24</a>
specifications ( <i>continued</i> )	
call control protocol .....	<a href="#">20</a>
codec .....	<a href="#">20</a>
dial plan .....	<a href="#">30</a>
hardware .....	<a href="#">21</a>
physical system protection .....	<a href="#">26</a>
port and switch .....	<a href="#">19</a>
power .....	<a href="#">18</a>
software .....	<a href="#">20</a>
temperature and humidity .....	<a href="#">25</a>
traffic .....	<a href="#">18</a>
support .....	<a href="#">35</a>
<b>T</b>	
temperature and humidity specification .....	<a href="#">25</a>
TLS .....	<a href="#">31</a>
traffic specification .....	<a href="#">18</a>
Transport Layer Security .....	<a href="#">31</a>
types of users	
essential .....	<a href="#">12</a>
everyday .....	<a href="#">12</a>
navigators .....	<a href="#">12</a>
walkup .....	<a href="#">12</a>
<b>V</b>	
Virtual Private Network .....	<a href="#">32</a>
Virus malware related attacks .....	<a href="#">33</a>
VPN .....	<a href="#">32</a>
<b>W</b>	
walkup users .....	<a href="#">12</a>